

Optiquest® Q201wb

20" WIDESCREEN LCD
WITH SUPER-FAST 5MS VIDEO RESPONSE

Affordable widescreen performance.

The Optiquest® Q201wb 20" widescreen LCD is the big screen choice for users on a budget. You won't sacrifice performance for price with this display. It combines high brightness and contrast ratio with SUPER-FAST 5MS VIDEO RESPONSE for crystal-clear, blur free video, text and graphics. The super-high 1680x1050 resolution reduces eyestrain and ensures text and graphics are crisp. The widescreen that lets you work in two applications or documents side-by-side, enhancing your productivity. The integrated power supply and VESA® wall-mount compliance reduce clutter and free up valuable desktop real estate. Furnish your desktop in style with the budget-friendly, feature-rich Q201wb.



ENHANCE YOUR PRODUCTIVITY

- > Super-fast 5ms video response delivers superior picture clarity
- > High brightness and contrast ratio
300-nit brightness (typ) and 1000:1 contrast ratio (typ) for rich, detailed images.
- > 1680x1050 optimum resolution
Incredible image detail for sharp text and graphics.
- > Stylish slim-bezel design
An ultra-thin bezel lets you see more without taking up valuable desktop space.
- > OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Full 20" viewable widescreen
Displays a full, flat 20" viewable widescreen area with crisp detail and fully saturated color.
- > Integrated power supply
- > VESA® 75mm wall-mount compliant
- > 24/7 free technical support and customer support*
- > PC and Mac® compatible



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

Optquest® Q201wb

20" WIDESCREEN LCD WITH SUPER-FAST 5MS VIDEO RESPONSE



| | | |
|-------------------------------|---|---|
| LCD | Type | 20" color TFT active matrix WXGA LCD |
| | Display Area | 17.1" horizontal x 10.7" vertical; 20.1" diagonal |
| | Optimum Resolution | 1680x1050 |
| | Contrast Ratio | 1000:1 (typ) |
| | Viewing Angles | 170° horizontal, 160° vertical @ contrast ratio > 10:1 |
| | Response Time | 5ms (typ) |
| | Light Source | Long life, 40,000 hrs. (typ) |
| | Brightness | 300 cd/m ² (typ) |
| | Panel Surface | Anti-glare |
| VIDEO INPUT | Analog | RGB analog (75 ohms, 0.7 Vp-p) |
| | Frequency | F _H : 30~80kHz, F _V : 55~75Hz |
| | Sync | H/V separated (TTL) |
| COMPATIBILITY | PC | VGA up to 1680x1050 non-interlaced |
| | Mac®** | G3/G4/G5 up to 1680x1050 |
| CONNECTOR | Analog | 15-pin mini D-sub |
| | Power | 3-pin AC plug (CEE22) |
| POWER | Voltage | AC 100~240V (universal), 50~60Hz (auto switch) |
| | Consumption | 45W (typ) |
| ERGONOMICS | Tilt | -5°/+15° |
| CONTROLS | Basic | Power, 2, up, down, 1 |
| | OnView® | Auto image adjust, brightness, contrast, color adjust (sRGB, 9300K, 6500K, 5400K, user color), H. position, V. position, H. size, OSD position, OSD timeout, OSD background, fine tune, sharpness, language, input select, recall |
| OPERATING CONDITIONS | Temperature | 32~104°F (0~40°C) |
| | Humidity | 20~80% (non-condensing) |
| DIMENSIONS (W x H x D) | Physical with stand | 19.1" x 16.1" x 8.0" (486mm x 409mm x 204mm) |
| | Physical without stand | 19.1" x 13.6" x 3.1" (486mm x 345mm x 79mm) |
| WEIGHT | Net with stand | 10.3 lb. (4.7 kg) |
| | Net without stand | 9.5 lb. (4.3 kg) |
| | Gross with stand | 12.8 lb. (5.8 kg) |
| REGULATIONS | UL, cUL, FCC-B, NOM, ENERGY STAR®, TUV-S | |
| RECYCLE/DISPOSAL | The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. | |
| POWER MANAGEMENT | ENERGY STAR® standards | |
| PACKAGE CONTENTS | LCD display, power cable, video cable, User Guide | |
| WARRANTY | One-year limited warranty on parts, labor and backlight | |



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic®
See the difference® 

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Excluding major U.S. holidays. **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [13757-01B-12/07] Q201wb-1

For more product information, visit us on the web at ViewSonic.com